



Specifications

Case

- Constructed using a combination of wood placement dowels and metal lock dowels with cams/bolts. Panels are 3/4" 45# particleboard that is laminated (TFL or HPL) on both sides, based on specification. All exposed edges are 3mm PVC.
- Shelves over 28" W are 1" thickness.
- Locking doors are standard for all models.
- Casters: 4" soft tread constructed of high tech thermoplastic elastomer for added traction on hard surfaces.
- 1" re-moveable caster plate is standard.
- Clear shelf clips are rated at 300 lb capacity per set.
- All models ship fully assembled, with trays inserted when specified. Over-sized tops attach in field.
- Standard top size for 36" is nominal 35" (to fit through standard doorways)
- 5" Arch pull is standard— Nickel or Black.
- European hinges with multiple adjustments are standard for all doors.

Edgebanding

Machine applied using PUR adhesive (moisture –curing, polyurethane, containing no (VOC's). All exposed edges are 3mm PVC.

Finishes

CFC Educational: Woodgrains—Solids—Nebulas—Patterns

Other Standard finish HPL: Upcharge may apply [*See pricelist for 721/722/723 Series*](#)

Options

(MG) Marker—Gloss only (MM) Marker—Magnetic (White or Light Gray only)

Tray/Runner color standard: Clear *Other colors available*

(P) Power units

