

Fully Welded Tables 140 Series



Depths	18", 20", 24", 30", 35, 42", 48"
Widths	32", 42", 54", 60", 72"

Heights	Desk	Stool	Bar
Levelers	20-32"	28-38"	33-43"
Casters	23-35"	31-41"	36-46"

Specifications

Frame	Fully unitized frame, wire welded, 16 gauge tubular steel construction with 1-1/2" square tubing, butt welded to form a solid rectangular support frame under the top surface. Inserts are 1-1/4" 16 gauge steel tubing. Screw type floor levelers are standard.		
Frame Finish	Frame is finished with electrostatically applied powdercoat. Applied polyester powdercoat to be 2-3 mils in thickness and provide maximum chemical solvent, and UV resistance. Scratch resistance of finish to meet pencil hardness test of 2H or better. Standard Finishes: (6) Premium Finishes: (12)		
Work Surface Options	Standard Grade Standard HPL (3mm PVC) High Wear HPL (3mm PVC)	Chemical Grade Chemsurf HPL (3mm PVC) Phenolic HPL (Black Edge)	Butcher Block Natural Hardwood with Clear Finish
Edgebanding	Machine applied using PUR adhesive (moisture-curing, polyurethane, containing no VOC's).		
HPL Edge Options	(3) 3mm PVC (R) Rolled Edge		
Casters	3" Soft Tread constructed of high tech thermoplastic elastomer for extra traction on hard surface floors.		