



8300 Series - Steel Base Desk

Model: 527



The 527 creates all-around value for any classroom. The wire management lends these desks to be placed end-to-end for continuous connection in any room.

Standard Sizes:

Depth: 20", 24", 30"

Width: 36", 42", 48", 60", 72"

Adjustable Height: 24-32", in 2" increments

Finishes and Specifications

Frame: Fully unitized frame, wire welded, 16 gauge tubular steel construction with 1" x 2" legs connected by 2" x 2" cross-member. Frame finished with electrostatically applied powdercoat 2-3 mils in thickness. Scratch resistance to meet 2H or better. Heavy duty floor levelers are standard. *Ships assembled.*

Edgebanding: Machine applied using a moisture-curing, polyurethane adhesive, containing no VOC's. 3mm PVC is standard on all panels. Matching tape is available.

Adjustable Legs: 14 gauge steel tubing with a telescopic insert of 16 gauge steel tubing. Legs are adjustable on 2" increments to allow height adjustment from 20-36". Legs lock with threaded insert screw. Legs equipped with a screw type guide.

Worksurface: Manufactured using 1" thick, 45lb. industrial grade particleboard. Exterior surface is high pressure laminate 0.030 and is applied to core with water resistant adhesive containing no VOC's. A backer sheet is applied to provide balanced construction.

Available Options: Front Roll Edge is standard. Comfort Edge or all 3mm PVC are available.

Wire Management: Manufactured of laminated particle board. Trough is mounted to underside of the work surface and to the frame and is fully accessible. Grommets are placed in the top. End of trough is open for ease of access and side-by-side design or can be capped, with grommet included.

Several options are available for this product, such as:

- Keyboard/Mouse/Pencil Tray
- Casters
- CPU Holder
- Book Bag Hook
- Power Strip
- Wire Management End Cap



Visit www.corilam.com for more information or email us at info@cfceducational.com

CORILAM FABRICATING COMPANY P.O. BOX 361 KERNERSVILLE, NC 27285

SL-527.01

July 2015

